



QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX® Sand Mix is a specially formulated blend of Portland cement and sand ideal for use where a thickness of one inch to two inches is required. All ingredients are thoroughly pre-mixed to ensure maximum strength and workability. Simply add water. Achieves 3,500 psi compressive strength as required in ASTM C-387 when used as directed.

Suggested Uses:

- ▶ Concrete Floor Topping
- ▶ Parging
- ▶ Repairing Walls
- ▶ Grouting
- ▶ Laying Flagstones & Paving Brick
- ▶ Fill Cracks
- ▶ Stuccoing
- ▶ Repair Floors
- ▶ Filling Tree Cavities

Preparation:

All surfaces should be clean and free of oil, gas, paint, grease, loose material etc., before applying mix. Smooth surfaces should be roughened with a wire brush.

Directions for Mixing:

Pour the necessary amount of PAKMIX® Sand Mix into a clean wheelbarrow, mortar box or similar easy-to-use container. Form a crater with a shovel or hoe in the center of the dry mix. Pour clean water into the crater at the rate of approximately one (1) quart per 15 lbs. of dry material. If the mix is too stiff, add water one cup at a time. Too much water will weaken the mix.

Items you may need:

- ▶ Mortar Box or Wheelbarrow
- ▶ Trowel and/or Float
- ▶ Shovel or Hoe
- ▶ Tools & Materials for Building Forms

Packaging & Yields:

80 lb. bag yields approximately 8 sq. ft. x 1" thick or 2/3 cu. ft. wet volume.

60 lb. bag yields approximately 6 sq. ft. x 1" thick or 1/2 cu. ft. wet volume.

For Best Results:

Use only when temperature is 40° F and above. In cold weather use warm – not hot water for mixing.

Apply freshly mixed PAKMIX® Sand Mix immediately. Do not retemper the mix after initial mixing.

When patching or resurfacing, it is important to dampen the surface of the existing concrete before applying the new material. The use of PAKMIX® Cement Fortifier and PAKMIX® Concrete



Glue for enhanced bonding is beneficial. The use of Pakmix® Cure & Seal is recommended.

Allow the new concrete to set firmly, then keep moist for at least three (3) days by an occasional fine spraying with water. Covering the area with a plastic film or damp burlap is recommended.

Clean Up:

Clean up is easy with soap and water. Rinse tools before material hardens.



Caution:

PAKMIX® Sand Mix contains Portland cement. As with any cement materials, direct contact may irritate eyes and skin. Wear protective clothing, gloves and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

Harmful if inhaled. This product contains Free Silica (CAS# 14808-60-7). When Free Silica is inhaled, it may cause delayed respiratory and other health problems. Free Silica has been listed by I.A.R.C. as a possible carcinogen based upon laboratory animal test data and limited evidence of human carcinogenicity. Avoid breathing cement dust. Keep the bag closed when not in use, and use only in well-ventilated areas. Follow OSHA Safety and Health Standards for crystalline silica. If the product must be used in an enclosed area, use a NIOSH approved dust respirator.

Keep Out of Reach of Children:

Material safety data sheet available upon request.



605 Industrial Way, Dixon, California 95620
(800) 272-5649 • FAX (707) 693-9349
www.pakmix.com

SAND MIX
PRO LINE

S
A
N
D
M
I
X